



TECHNICAL DATA SHEET

PRODUCT NAME

Series 1 Acrylate Primer

DESCRIPTION

This product is a specialized primer for acrylic radiative cooling coating with extremely high infrared reflectivity. It reflects longer-wavelength near-infrared rays that penetrates the topcoat, enabling a thinner composite coating system to reflect the entire solar spectrum, including ultraviolet, visible, and near-infrared light. When used in conjunction with radiation cooling topcoats, the coating achieves extremely high solar reflectance and radiates heat into outer space with high emissivity. Applied on building roofs, walls, or outdoor equipment surfaces, it can reduce surface temperatures by 3-8 °C below ambient temperatures even during hot summers, lowering air conditioning energy consumption, alleviating energy shortages, reducing carbon emissions, and promoting sustainable development.

TYPE

Water based acrylic paint

COLOUR

White Only

USEAGE

Widely applicable in building energy efficiency, data centers, grain storage, petrochemical storage tanks, power equipment, cold chain logistics, and new energy sectors where temperature-sensitivity or cooling/energy savings are required.

Features

- Extremely high near-infrared reflectance and heat radiation capabilities.
- Excellent adhesion to various substrates such as concrete and metal.
- Superior alkali resistance and weather resistance.
- Strong hiding power and excellent water resistance.
- Easy to apply, water-based, and environmentally friendly.
- Singapore Green Label compliant.
- SS579 compliant.

PRODUCT DATA

Packaging size	5 Kg and 20 Kg containers
Specific gravity	1.4 ± 0.1 kg/litre
VOC	<2 g/l
Volume solid	55%
SHELF LIFE	12 months from the production date

APPLICATION DATA



TECHNICAL DATA SHEET

The product can be applied by

Roller, brush, airless spray.

Stir the paint thoroughly before application.

SURFACE PREPARATION

Remove surface dust, oil, and loose materials. Rinse with water and allow it to dry naturally. Repair cracks and holes with cement mortar, then sand the surface to achieve a rough texture.

APPLICATION CONDITIONS

Avoid application in humid or cold weather (temperature below 5 °C or above 35 °C, relative humidity above 85%), as it may affect the coating performance. Ensure proper drying time between coats. Applying the next coat too soon may cause slow drying, wrinkling, bubbling, and poor water resistance and adhesion.

DRYING TIME

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.

1. In case of multiple coat application, drying time will be influenced by the number and sequence and by the total thickness of previous coats applied
2. The surface should be dry and free from any contamination prior to application of the subsequent coat.

RECOMMENDED COATING SYSTEM AND THEORETICAL COVERAGE

Coating Step	Coating Name	Number of Coats	Practical Paint Consumption (m ² /KG per coat)
Primer	PasteCool® Series 1 Primer	2	6-7
Topcoat	PasteCool® Series 3 or 4 Topcoat	1	6-8

Note: Evaluation based on smooth surface, dry film thickness ~50 micron.

CLEANING INSTRUCTIONS

Clean all tools with water immediately during pauses or completion of coating.

PRECAUTIONS

Wear protective gloves, masks, and goggles during application. Avoid skin and eye contact. In case of contact, rinse immediately with plenty of water and seek medical attention if necessary.

STORAGE

Store in a cool, dry, and well-ventilated place at 5-35 °C, away from direct sunlight and freezing temperatures. Seal tightly to prevent moisture loss.



TECHNICAL DATA SHEET

SAFETY INFORMATION

Before using this product, always read the safety information on the packaging and in the Safety Data Sheet (SDS)

- **Ventilation:** Ensure good ventilation during the application and drying to minimize inhalation.
- **Personal protection:** Avoid direct contact with skin and eyes. Wear suitable personal protective equipment (PPE) such as gloves, goggles and, if spraying, a respirator.
- **First aid:** If paint contacts skin, wash immediately with soap and water. If it enters the eyes, rinse thoroughly with clean water and seek medical attention.
- **Fire safety:** For solvent based or flammable products, keep away from naked flames, sparks, welding operations, and smoking areas.
- **Spillage:** Clean up spills promptly using appropriate cleaning agents.
- **Suitability:** If unsure about the product's application or compatibility, consult the manufacturer for guidance.

DISCLAIMER

The information in this data sheet is given to the best of Entropy lab's knowledge, based on laboratory testing and practical knowledge. Users may consult with Entropy Lab on the general suitability of the product for their needs and specific application practices and as such, products are often used under conditions beyond Entropy Lab control. Entropy Lab cannot guarantee anything but the quality of the product itself. In line with Entropy Lab policy for continuous development, Entropy Lab reserves the right to modify the product and the information in this data sheet without prior notice. It is the user's responsibility to check with Entropy Lab for the latest version of this data sheet.

Users should always consult Entropy Lab for specific guidance on the general suitability of this product for their needs and specific application practices.